

| Client | Quantity |
|---------|----------|
| Project | Position |

Roll-in

Model: J100/1M Cod: J11100200101



Roll-in refrigerated cabinet for GN2/1 trolleys, 1 door. Plug-in refrigeration unit, 5 heavy duty climatic class and R290 ecological refrigerant gas. Led lighting, snap handle with lock and key as standard. Temperature range -2°+8°C with ventilated refrigeration hot gas defrost. 75 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free); easily replaceable triple chamber magnetic gasket. One-piece structure, interior/exterior AISI 304 stainless steel, exterior galvanised steel back. Rounded inner corners for easy cleaning. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Predisposed for connection to Cosmo remote supervision system and ModBus/RTU Rs485 connection.

Technical data

| Gross capacity: | 754 lt |
|---------------------|---------------------------------|
| Temperature range: | -2°+8°C |
| Refrigerant unit: | Plug-in |
| Climate class: | 5 |
| Cooling gas: | R290 (GWP=3) |
| Refrigerant Charge: | 80g |
| Defrost: | Hot gas |
| Valve: | Supplied standard with solenoid |
| Dimensions: | 810×815×2115 mm |
| Packing dimensions: | 840×920×2260 mm |
| Net / gross weight: | 130 Kg / 150 Kg |
| Net / gross volume: | 353 lt / 754 lt |
| Voltage: | 220-240 V - 50 Hz |
| Total rate: | 390W - 1,8A |
| Cooling capacity: | 713 W* |
| *: | Evap10°C Cond. +55°C |

Features

| Standard equipment: | LED lighting, lock with key |
|------------------------------|--|
| Control: | Electronic, display flush with the panel |
| Doors: | 1 door, self-closing with a 105° stop, right hinged |
| Door gasket: | Magnetic, triple chamber and easily replaceable |
| Insulation: | 75 mm thickness - CFC/HCFC free |
| Exterior/interior finishing: | One-piece structure in AISI 304 stainless steel. Back in galvanized steel |
| Inner corners: | Rounded for easy cleaning and ensuring maximum |
| | hygiene |
| Handle: | Snap-in chrome with integrated lock |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants

Alimentazione frequenza 60Hz


Trolley GN2/1 20 trays 598x660x1630 mm

Other special voltage Cosmo cable connection kit

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The cabinet, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw



A: Power supply cable outlet

Condensation water drain

B:

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.