

Client	Quantity
Project	Position

Tavolo Snack GN 3 porte BT

Model: TP16/1B-490 Cod: T10381000404



Technical data

_	APPL 4
Тор:	With top
Gross capacity:	278 lt
Temperature range:	-15°-22°C
Refrigerant unit:	Plug-in
Energetic class:	D
Energy efficiency index:	51,3
Annual consumption:	1535 kW/h annum
24h consumption:	4,205 kW/h/24h
Climate class:	5
Cooling gas:	R290 (GWP=3)
Refrigerant Charge:	
Defrost:	Hot gas
Body height:	490 mm
Valve:	Supplied standard with solenoid
Dimensions:	1600×700×630 mm
Packing dimensions:	1875×800×998 mm
Net / gross weight:	140 Kg / 150 Kg
Net / gross volume:	158 lt / 278 lt
Voltage:	220-240 V - 50 Hz
Total rate:	850W - 3,9A
Cooling capacity:	569 W*
*:	Evap30°C Cond. +55°C

Features

Standard equipment:	3 slides, 3 plastic coated GN1/1 shelves
Control:	Electronic, display flush with the panel
Doors:	3 doors, self-closing, reversible with 105° stop
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants


Drawers 1/1 Drawers 1/2 Special size of technical compartment Drawers 1/1 Drawers 1/2 Technical compartment on the left Lock with key for drawer 1/1 Special size of technical compartment Technical compartment on the left Lock with key for drawer 1/2 RAL customisable colouring Lock with key for drawer 1/1 Lock with key for drawer 1/2 Plug-in water unit Alimentazione frequenza 60Hz RAL customisable colouring Plug-in water unit

Other special voltage Alimentazione frequenza 60Hz Other special voltage Adjustable feet h 145/195 mm 4 Swivel and brake castors h 128 mm Brackets for GN pans for drawer GN1/2 container + lids kit for drawer, h 150 mm GN1/3 container + lids kit for drawer, h 150 mm Bottles shelf, stainless steel coating for shelf 350 Stainless steel shelf GN1/1 Plastic coated shelf GN1/1 Pair of type C slides 505 mm IP44 schuko socket with cover Serial interface, RS485 cable Cosmo cable connection kit Cosmo wifi connection kit Removable plinth GN 2D h 100 mm

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw



In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.