

Client _____ Quantity _____

Project _____ Position _____

Tavolo Snack GN 3 porte BT

Model: TP16/1BR-490

Cod: T10391000404



Technical data

| | |
|---------------------|---------------------------------|
| Top: | With top |
| Gross capacity: | 278 lt |
| Temperature range: | -15°-22°C |
| Refrigerant unit: | remote |
| Cooling gas: | R452a (GWP=2.141) |
| Defrost: | Electric |
| Body height: | 490 mm |
| Valve: | Supplied standard with solenoid |
| Dimensions: | 1600×700×630 mm |
| Packing dimensions: | 1875×800×998 mm |
| Net / gross weight: | 115 Kg / 125 Kg |
| Net / gross volume: | 158 lt / 278 lt |
| Voltage: | 220-240 V - 50-60 Hz |
| Total rate: | 920W - 4,2A |
| Cooling capacity: | 540 W* |
| *: | Evap. -30°C Cond. +55°C |

Features

| | |
|------------------------------|--|
| Standard equipment: | 3 slides, 3 plastic coated GN1/1 shelves |
| Control: | Electronic, display flush with the panel |
| Doors: | 3 doors, self-closing, reversible with 105° stop |
| Door gasket: | Magnetic, triple chamber and easily replaceable |
| Insulation: | 60 mm thickness - CFC/HCFC free |
| Exterior/interior finishing: | Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. |
| Inner corners: | Rounded for easy cleaning and ensuring maximum hygiene |
| Handle: | Stainless steel AISI 304, 2 mm thick |
| Racks and slides: | Stainless steel AISI 304 |
| Feets: | AISI 304 stainless steel adjustable h 100/150 mm |
| Cosmo: | Predisposed for Cosmo Hub connection |

Accessories and variants

| | |
|--|--|
| Drawers 1/1 | RAL customisable colouring |
| Drawers 1/2 | Predisposition for connection to CO2 remote control unit |
| Special size of technical compartment | Alimentazione frequenza 60Hz |
| Drawers 1/1 | Other special voltage |
| Drawers 1/2 | Remote condensing unit NT2178GK |
| Technical compartment on the left | Adjustable feet h 145/195 mm |
| Common technical compartment | 4 Swivel and brake castors h 128 mm |
| Special size of technical compartment | Brackets for GN pans for drawer |
| Technical compartment on the left | GN1/2 container + lids kit for drawer, h 150 mm |
| Counters without a technical compartment | GN1/3 container + lids kit for drawer, h 150 mm |
| Lock with key for drawer 1/1 | Bottles shelf, stainless steel coating for shelf 350 |
| Common technical compartment | Stainless steel shelf GN1/1 |
| Counters without a technical compartment | Plastic coated shelf GN1/1 |
| Lock with key for drawer 1/2 | Pair of type C slides 505 mm |
| Lock with key for drawer 1/1 | Serial interface, RS485 cable |
| Lock with key for drawer 1/2 | Cosmo cable connection kit |
| Lock with key for drawer 1/2 | Cosmo wifi connection kit |
| Alimentazione frequenza 60Hz | Removable plinth GN 3DR h 100 mm |
| Other special voltage | Removable plinth GN 3DR h 150 mm |

Remote unit technical data

| | |
|----------------------------|-------------------------|
| Voltage: | 220-240 V - 50 Hz |
| Assorbimento Unità Remota: | 650W - 3,0A |
| Cooling gas: | R452A |
| Gross weight: | 25,7 Kg |
| Dimensions: | 500×330×295 mm |
| Pipe delivery: | Ø 3/8" |
| Pipe suction: | Ø 3/8" |
| Packing dimensions: | 540×345×310 mm |
| Cooling capacity: | Evap. -30°C Cond. +55°C |

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw

