

Client _____ Quantity _____

Project _____ Position _____

Retarder-prover Vision counter with 3 doors

Model: TFP17/1MJ-760

Cod: T60361000802



Technical data

| | |
|--------------------------|---------------------------------|
| Top: | With top |
| Max capacity: | 21 trays E |
| Gross capacity: | 658 lt |
| Temperature range: | -6°+40°C |
| Humidity range: | 45% - 95% with humidifier |
| Humidifier: | Including |
| Refrigerant unit: | Plug-in |
| Energetic class: | D |
| Energy efficiency index: | 59,0 |
| Annual consumption: | 1690 |
| 24h consumption: | 4631 |
| Climate class: | 5 |
| Cooling gas: | R290 (GWP=3) |
| Refrigerant Charge: | 110g |
| Defrost: | Hot gas |
| Body height: | 760 mm |
| Valve: | Supplied standard with solenoid |
| Dimensions: | 2005×800×900 mm |
| Packing dimensions: | 2100×900×998 mm |
| Net / gross weight: | 199 Kg / 209 Kg |
| Net / gross volume: | 418 lt / 658 lt |
| Voltage: | 220-240 V - 50 Hz |
| Total rate: | 550W - 2,5A |
| Cooling capacity: | 565 W* |
| *: | Evap. -10°C Cond. +55°C |

Features

| | |
|------------------------------|---|
| Functions: | Retarder prover, manual proving, continuous cycle, storage, chocolate, thawing, ice cream |
| Standard equipment: | 21 slides EN60x40 |
| Control: | 7" touch screen display with USB port |
| Doors: | 3 doors, self-closing, reversible with 105° stop |
| Door gasket: | Magnetic, triple chamber and easily replaceable |
| Insulation: | 60 mm thickness - CFC/HCFC free |
| Exterior/interior finishing: | Exterior and interior AISI 304 stainless steel. |
| Inner corners: | Rounded for easy cleaning and ensuring maximum hygiene |
| Handle: | Stainless steel AISI 304, 2 mm thick |
| Racks and slides: | Stainless steel AISI 304, quick release |
| Feets: | AISI 304 stainless steel adjustable h 100/150 mm |
| Cosmo: | Wi-Fi remote control system |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.

Accessories and variants

| | |
|---------------------------------------|--|
| RAL customisable colouring | 6 Swivel and brake castors h 128 mm |
| Plug-in water unit | Aluminium coated backingan EN60x40 h 20 mm |
| Alimentazione frequenza 60Hz | Stainless steel shelf EN60x40 |
| Other special voltage | Plastic coated shelf EN60x40 |
| Purity C Quell ST 50 filter cartridge | Pair of type L slides 402 mm EN |

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows VISION retarder provers to be connected, updated and monitored from smartphones. VISION is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

Technical draw

