Client _____ Quantity _____

Project _____ Position _____

Display case for ingredients 1795 mm

Model: YP18/8NLR **Cod:** V42181100001

Display case for ingredients without glass, width 1795 mm for GN1/3 trays (excluded). Range of temperature 0°+10°C with remote refrigeration unit and R452a refrigerant gas. Exterior and interior AISI 304 stainless steel, water condensation drain, 30 mm insulation thickness HFO with high insulation performance and low environmental impact (CFC-, HCFC-, HFC-free). Ready for connection to Cosmo remote supervision system and ModBus/RTU Rs485 connection. Allows installation on the granite splashback of pizza counters, on stainless steel feet or fixed to the wall (optional).



Technical data

Gross capacity:	68 lt
Temperature range:	+2°+10°C
Refrigerant unit:	remote
Cooling gas:	R452a (GWP=2.141)
Valve:	Supplied standard with solenoid
Dimensions:	1795×380×275 mm
Packing dimensions:	1855×450×490 mm
Net / gross weight:	35 Kg / 45 Kg
Net / gross volume:	/ 68 lt
Voltage:	220-240 V - 50-60 Hz
Total rate:	22W - 0,1A
Cooling capacity:	368 W*
*:	Evap. -10°C Cond. +55°C

Features

Control:	Electronic, display flush with the panel
Insulation:	30 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior and interior AISI 304 stainless steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.

Accessories and variants

- Alimentazione frequenza 60Hz
- Other special voltage
- Remote condensing unit EMT6144GK
- Lid for overnight storage of ingredients GN1/3 1373x302x20
- 1795 display case pans kit, GN1/3
- Wall clamps, 2 pieces
- Kit of 4 stainless steel feets
- Cosmo cable connection kit
- Cosmo wifi connection kit
- Pan GN1/2 325x265x150 mm
- Lid for GN1/2 pan
- Pan GN1/3 325x176x150 mm
- Lid for GN1/3 pan
- Pan GN1/6 176x162x150 mm
- Lid for GN1/6 pan
- Pan GN1/9 176x108x100 mm
- Lid for GN1/9 pan
- Pan GN2/8 325x132x150 mm
- Lid for GN2/8 pan
- Brackets for pans 20 mm GN1/3
- Brackets for pans 25 mm GN1/3
- Brackets for pans 30 mm GN1/3


Remote unit technical data

Voltage:	220-240 V - 50 Hz
Unit total rate :	250W - 1,1A
Cooling gas:	R404-R452
Gross weight:	17 Kg
Dimensions:	450×300×270 mm
Pipe delivery:	Ø 1/4"
Pipe suction:	Ø 3/8"
Packing dimensions:	470×330×300 mm
Cooling capacity:	Evap. -10°C Cond. +55°C

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The display case for ingredients, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw



A: Power supply cable outlet

B: Condensation water drain

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.