

Client	Quantity
Project	Position

Vision Industry W35K NUVO

Model: W35KHR Cod: W82110112002



Technical data

Max capacity:	1 trolley
	-40°+85°C
Temperature range:	-40°+85°C
Ventilation range:	25% - 100%
Humidity range:	45% - 95% with humidifier
Humidifier:	Including
Refrigerant unit:	remote
Yield +90/+3:	100 Kg
Yield +90/-18:	80 Kg
Cooling gas:	R404/R452
Defrost:	Forced air
Valve:	Electronic expansion valve
Dimensions:	1230×1200×2510 mm
Packing dimensions:	1464×1364×2550 mm
Net / gross weight:	310 Kg / 340 Kg
Net / gross volume:	/
Voltage:	400-415 V - 50-60 Hz
Total rate:	3170 W - 12,46 A
Cooling capacity:	11010 W*
*:	Evap10°C Cond. +45°C

Features

Functions:	Blast chilling, shock freezing, thawing, proving and retarder prover, holding, steam pasteurisation, low temperature steam cooking, steam sanitizing, manual steam cycle
Control:	7" touch screen display with USB port
Door gasket:	Magnetic, triple chamber and easily replaceable
Core probe:	Needle probe with 1 reading point, quick-release and easily replaceable
Insulation:	100 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Internal and external in "linen canvas" steel
Inner corners:	Rounded base 20 mm
Handle:	In AISI 304 stainless steel
Cosmo:	Wi-Fi remote control system

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants

Abbattitore fornito smontato	C
Floor 20 mm high, ramp included	(
Reverse door opening from standard	9
Door opening turning and control panel inversion	+ F
Door stop 100°	F
Sonda al cuore 3 punti di lettura	F
Sonda al cuore riscaldata 1 punto di lettura	1
Winter kit -20°C	1
Winter kit -40°C	F

Other	special voltage
Open	remote condensing unit 4EES-4Y
	ed faired remote condensing unit 4EES-4Y er kit -20°
PVC v	entilation profiles W35K
Ramp	100 mm high. Length 913 mm W35
Ramp	140 mm high. Length 1390 mm W35
Trolley	y GN1/1 20 trays 598x530x1630 mm
Trolley	y EN60x40 20 trays 460x620x1750 mm
Purity	C Quell ST 50 filter cartridge


Remote unit technical data


Voltage:	400-415 V 3N - 50 Hz
Assorbimento Unità Remota:	4,98kW - 10,1A
Cooling gas:	R404-R452a
HP unit:	4
Gross weight:	187 Kg
Dimensions:	1110×785×626 mm
Pipe delivery:	12 mm
Pipe suction:	28 mm
Cooling capacity:	Evap10°C Cond. +45°C


COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows VISION blast chillers to be connected, updated and monitored from smartphones. VISION is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

Technical draw







- Power supply cable outlet
- Condensation water drain

W:

C: Floor grid for condensate drainage (recommended)

- I: Internal led lighting
- L: Door clear opening dimension
- N: PVC ventilation profiles

Gas output pipes

R:

Water mains connection for humidifier - 3/4" female. Unloading not required

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.