

Client	Quantity	
5	` '	
Project	Position	

Master 700 XL cabinet

Model: AS70/1BV Cod: A14070600602



Master 700 XL refrigerated cabinet, 1 door. Plug-in refrigeration unit, E energetic class, 4 climatic class and R290 ecological refrigerant gas. Equipment: 3 650x588 $\,$ mm plastic coated shelves, lock with key, led strip lighting. Temperature range - $18^{\circ}\text{-}22^{\circ}\text{C};$ ventilated refrigeration. The sturdy moulded slides, attached to the sides of the chamber, allow rapid repositioning of the XL shelves into the $7\,$ available levels, providing +10% extra storage space for ingredients and semifinished products. Anti-corrosion treated evaporator, hot gas defrost. 75 $\mbox{\sc mm}$ insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). Black plastic handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening with 105° stop. One-piece structure, interior/exterior AISI 304 stainless steel; outside back, external base and inside technical compartment in galvanised/colaminated steel. rounded inner corners for easy cleaning. The reinforced modular base in colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Predisposed for connection to Cosmo remote supervision system and ModBus/RTU Rs485 connection.

Technical data

Gross capacity:	601 lt
Temperature range:	-18°-22°C
Refrigerant unit:	Plug-in
Energetic class:	E
Energy efficiency index:	82,0
Annual consumption:	3223 kW/h annum
24h consumption:	8,830 kW/h/24h
Climate class:	4
Cooling gas:	R290 (GWP=3)
Refrigerant Charge:	150g
Defrost:	Hot gas
Valve:	Supplied standard with solenoid
Valve: Dimensions:	Supplied standard with solenoid 740×815×2085 mm
Dimensions:	740×815×2085 mm
Dimensions: Packing dimensions:	740×815×2085 mm 835×930×2138 mm
Dimensions: Packing dimensions: Net / gross weight:	740×815×2085 mm 835×930×2138 mm 150 Kg / 170 Kg
Dimensions: Packing dimensions: Net / gross weight: Net / gross volume:	740×815×2085 mm 835×930×2138 mm 150 Kg / 170 Kg 499 lt / 601 lt
Dimensions: Packing dimensions: Net / gross weight: Net / gross volume: Voltage:	740×815×2085 mm 835×930×2138 mm 150 Kg / 170 Kg 499 lt / 601 lt 220-240 V - 50 Hz
Dimensions: Packing dimensions: Net / gross weight: Net / gross volume: Voltage: Total rate:	740×815×2085 mm 835×930×2138 mm 150 Kg / 170 Kg 499 lt / 601 lt 220-240 V - 50 Hz 1000W - 4,6A

Features

Standard equipment:	3 slides for 650x588 mm shelves, 3 plastic coated 650x588 mm shelves, lock with key
Control:	Electronic, display flush with the panel
Doors:	1 aluminium door, self-closing with 105° latch, right-hand hinges
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	75 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior and interior AISI 304 stainless steel. Back, base and internal technical compartment in galvanized/colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	High-strength technopolymer guides fixed to the sides of the chamber
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants


Alimentazione frequenza 60Hz	
Other special voltage	
Half doors	
Frame for fixed masonry plinth	
RAL customisable colouring	
Master Marine solutions	
Predisposition for connection to CO2 remote control unit	

Plug-in water unit
Foot pedal kit
4 Swivel and brake castors h 128 mm
Plastic coated shelf 650x588 mm
Serial interface, RS485 cable
Cosmo cable connection kit
Cosmo wifi connection kit

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The cabinet, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw





A: Power supply cable outlet

D: Airflow conveyor

Racks pitch

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.