

| Client | Quantity |
|---------|----------|
| Proiect | Position |

Modi Active Blast Chiller

Model: W5AGSA Cod: W11057010011



Technical data

| Тор: | Thickness 4 cm. Reinforced in order to place an oven |
|---------------------|--|
| Gross capacity: | 114 lt |
| Temperature range: | -40°+65°C |
| Ventilation range: | 25% - 100% |
| Humidifier: | Not available |
| Refrigerant unit: | Plug-in water unit |
| Yield +90/+3: | 18 Kg |
| Yield +90/-18: | 10 Kg |
| Climate class: | 5 |
| Cooling gas: | R290 (GWP=3) |
| Defrost: | Hot gas |
| Valve: | Electronic expansion valve |
| Dimensions: | 780×700×853 mm |
| Packing dimensions: | 875×915×901 mm |
| Net / gross weight: | 110 Kg / 120 Kg |
| Net / gross volume: | / 114 lt |
| Voltage: | 220-240 V - 50 Hz |
| Total rate: | 1247 W - 6,5 A |
| Cooling capacity: | 1349 W* |
| *. | Evap10°C Cond. +40°C |
| Noise: | 59,4 dB |

Features

| Functions: | Blast chilling, shock freezing, thawing, proving, holding, desiccation, chocolate, manual cycle |
|------------------------------|---|
| Standard equipment: | 5 slides GN1/1, EN60x40 |
| Control: | 4,3" touch screen display with USB port |
| Doors: | Cushioned, with anti-odor system |
| Door gasket: | Magnetic, triple chamber and easily replaceable |
| Core probe: | Needle probe with 1 reading point, quick-release and easily replaceable |
| Insulation: | 60 mm thickness - CFC/HCFC free |
| Exterior/interior finishing: | Exterior and interior AISI 304 stainless steel. |
| Inner corners: | Rounded for easy cleaning and ensuring maximum hygiene |
| Handle: | Stainless steel AISI 304, 2 mm thick |
| Racks and slides: | Stainless steel AISI 304, quick release |
| Feets: | AISI 304 stainless steel adjustable h 100/150 mm |
| Cosmo: | Wi-Fi remote control system |
| | |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants

RAL customisable colouring

Sonda al cuore a 3 punti di lettura

Sonda al cuore riscaldata a 1 punto di lettura

Reverse door opening from standard

Alimentazione frequenza 60Hz

Other special voltage

Lowered foot h 55/70 mm

4 Swivel and brake castors h 128 mm

Stainless steel shelf GN1/1

Plastic coated shelf GN1/1


Stainless steel shelf EN60x40


Plastic coated shelf EN60x40


COSMO - wi-fi control


Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows MODI blast chillers to be connected, updated and monitored from smartphones. MODI is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

Technical draw









A: Power supply cable outlet

B: Condensation water drain

G: Racks pitch

W1: Water inlet/outlet for condensing unit - 3/4" male