

Client \_\_\_\_\_ Quantity \_\_\_\_\_  
Project \_\_\_\_\_ Position \_\_\_\_\_

## Modi Up Blast Chiller

Model: W6UGA

Cod: W11064010011

Modi multifunction blast chiller 6 trays Up version, depth 700 mm, temperature range -40°+10°C. It is equipped with the functions: blast chilling, blast freezing, manual cycle. Plug-In refrigeration system with water condensation with R290 ecological refrigerant gas. 4,3" touch screen on the door and operating mode with customisable recipes, by time or with core probe. Adjustable ventilation 25-100%. Blast chilling yield +90/+3°C - 24 Kg; blast freezing yield +90/-18°C - 18 Kg. 5 heavy duty climatic class, hot gas defrost. 60 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). Electronic expansion valve and anti-corrosion painted evaporator. Cushioned door with anti-odour system with Easily replaceable triple chamber magnetic gasket, core probe with screw connector and housing on the port. Exterior and interior AISI 304 stainless steel, fan unit and condenser cover removable without tools. Equipment: 6 positions for GN1/1 trays. ModBus/RTU Rs485 connection as standard. Cosmo: wi-fi connection for remote monitoring via Cosmo App. When wired to Coldline counters and cabinets acts as a hub for remote monitoring of connected equipment.



### Technical data

|                     |                                                      |
|---------------------|------------------------------------------------------|
| Top:                | Thickness 4 cm. Reinforced in order to place an oven |
| Gross capacity:     | 121 lt                                               |
| Temperature range:  | -40°+10°C                                            |
| Ventilation range:  | 25% - 100%                                           |
| Humidifier:         | Not available                                        |
| Refrigerant unit:   | Plug-in water unit                                   |
| Yield +90/+3:       | 24 Kg                                                |
| Yield +90/-18:      | 18 Kg                                                |
| Climate class:      | 5                                                    |
| Cooling gas:        | R290 (GWP=3)                                         |
| Defrost:            | Hot gas                                              |
| Valve:              | Electronic expansion valve                           |
| Dimensions:         | 710×700×913 mm                                       |
| Packing dimensions: | 805×800×1141 mm                                      |
| Net / gross weight: | 115 Kg / 125 Kg                                      |
| Net / gross volume: | / 121 lt                                             |
| Voltage:            | 220-240 V - 50 Hz                                    |
| Total rate:         | 1474 W - 6,4 A                                       |
| Cooling capacity:   | 2368 W*                                              |
| *:                  | Evap. -10°C Cond. +40°C                              |
| Noise:              | 60,4 dB                                              |

### Features

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Functions:                   | Blast chilling, shock freezing, continuous cycle                        |
| Standard equipment:          | Support for 6 positions GN1/1                                           |
| Control:                     | 4,3" touch screen display with USB port                                 |
| Doors:                       | Cushioned, with anti-odor system                                        |
| Door gasket:                 | Magnetic, triple chamber and easily replaceable                         |
| Core probe:                  | Needle probe with 1 reading point, quick-release and easily replaceable |
| Insulation:                  | 60 mm thickness - CFC/HCFC free                                         |
| Exterior/interior finishing: | Exterior and interior AISI 304 stainless steel.                         |
| Inner corners:               | Rounded for easy cleaning and ensuring maximum hygiene                  |
| Handle:                      | Stainless steel AISI 304, 2 mm thick                                    |
| Racks and slides:            | Structure in stainless steel wire AISI 304                              |
| Feets:                       | AISI 304 stainless steel adjustable h 100/150 mm                        |
| Cosmo:                       | Wi-Fi remote control system                                             |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.


### Accessories and variants

|                                                |                                     |
|------------------------------------------------|-------------------------------------|
| RAL customisable colouring                     | Other special voltage               |
| Sonda al cuore a 3 punti di lettura            | Lowered foot h 55/70 mm             |
| Sonda al cuore riscaldata a 1 punto di lettura | 4 Swivel and brake castors h 128 mm |
| Reverse door opening from standard             | Stainless steel shelf GN1/1         |
| Alimentazione frequenza 60Hz                   | Plastic coated shelf GN1/1          |

### COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows MODI blast chillers to be connected, updated and monitored from smartphones. MODI is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

### Technical draw



A: Power supply cable outlet

B: Condensation water drain

G: Racks pitch

W1: Water inlet/outlet for condensing unit - 3/4" male