

Client	Quantity
Project	Position

Saladette Arkis GN counter 1 door

Model: HA09/1MD-760 Cod: H80102000212



Technical data

_	
Тор:	With top and splashback
Gross capacity:	130 lt
Temperature range:	-2°+8°C
Refrigerant unit:	Plug-in
Cooling gas:	R290 (GWP=3)
Defrost:	Hot gas
Body height:	760 mm
Valve:	Supplied standard with solenoid
Dimensions:	820×700×1000 mm
Packing dimensions:	915×800×998 mm
Net / gross weight:	93 Kg / 103 Kg
Net / gross volume:	/ 130 lt
Voltage:	220-240 V - 50 Hz
Total rate:	250W - 1,15A
Cooling capacity:	406 W*
*:	Evap10°C Cond. +55°C

Features

Control: Electronic, display flush with the panel Doors: 1 door with 180° opening Door gasket: Magnetic, triple chamber and easily replaceable Insulation: 60 mm thickness - CFC/HCFC free Exterior/interior finishing: Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel.		
Doors: 1 door with 180° opening Door gasket: Magnetic, triple chamber and easily replaceable Insulation: 60 mm thickness - CFC/HCFC free Exterior/interior finishing: Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. Inner corners: Rounded for easy cleaning and ensuring maximum hygiene Handle: Stainless steel AISI 304, 2 mm thick Racks and slides: Stainless steel AISI 304	Standard equipment:	1 slide, 1 plastic coated GN1/1 shelf
Door gasket: Magnetic, triple chamber and easily replaceable Insulation: 60 mm thickness - CFC/HCFC free Exterior/interior finishing: Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. Inner corners: Rounded for easy cleaning and ensuring maximum hygiene Handle: Stainless steel AISI 304, 2 mm thick Racks and slides: Stainless steel AISI 304	Control:	Electronic, display flush with the panel
Insulation: 60 mm thickness - CFC/HCFC free Exterior/interior finishing: Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. Inner corners: Rounded for easy cleaning and ensuring maximum hygiene Handle: Stainless steel AISI 304, 2 mm thick Racks and slides: Stainless steel AISI 304	Doors:	1 door with 180° opening
Exterior/interior finishing: Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. Inner corners: Rounded for easy cleaning and ensuring maximum hygiene Handle: Stainless steel AISI 304, 2 mm thick Racks and slides: Stainless steel AISI 304	Door gasket:	Magnetic, triple chamber and easily replaceable
steel. Base in colaminated steel. Inner corners: Rounded for easy cleaning and ensuring maximum hygiene Handle: Stainless steel AISI 304, 2 mm thick Racks and slides: Stainless steel AISI 304	Insulation:	60 mm thickness - CFC/HCFC free
hygiene Handle: Stainless steel AISI 304, 2 mm thick Racks and slides: Stainless steel AISI 304	Exterior/interior finishing:	
Racks and slides: Stainless steel AISI 304	Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
	Handle:	Stainless steel AISI 304, 2 mm thick
Feets: AISI 304 stainless steel adjustable h 100/150 mm	Racks and slides:	Stainless steel AISI 304
	Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo: Predisposed for Cosmo Hub connection	Cosmo:	Predisposed for Cosmo Hub connection


In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.





COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw









- A: Power supply cable outlet
- B: Condensation water drain
- G: Racks pitch

J: Automatic evaporation of condensing water