

Client	Quantity
Project	Position

Master Fish 700 cabinet

Model: A70/1P Cod: A14070300101



Technical data

	(04 l)
Gross capacity:	601 lt
Temperature range:	-6°+4°C
Refrigerant unit:	Plug-in
Energetic class:	В
Energy efficiency index:	34,1
Annual consumption:	460 kW/h annum
24h consumption:	1,26 kW/h/24h
Climate class:	5
Cooling gas:	R290 (GWP=3)
Refrigerant Charge:	104g
Defrost:	Hot gas
Valve:	Supplied standard with solenoid
Dimensions:	740×815×2085 mm
Packing dimensions:	835×930×2138 mm
Net / gross weight:	135 Kg / 155 Kg
Net / gross volume:	450 lt / 601 lt
Voltage:	220-240 V - 50 Hz
Total rate:	260W - 1,2A
Cooling capacity:	533 W*
*:	Evap10°C Cond. +55°C

Features

slides for GN2/1 shelves, 6 abs GN1/1 pans, lock vith key, LED lighting, water drain lectronic, display flush with the panel
lectronic, display flush with the panel
door, self-closing with a 105° stop, right hinged
Magnetic, triple chamber and easily replaceable
5 mm thickness - CFC/HCFC free
xterior and interior AISI 304 stainless steel. Back, ase and internal technical compartment in alvanized/colaminated steel.
counded for easy cleaning and ensuring maximum ygiene
tainless steel AISI 304, 2 mm thick
tainless steel AISI 304
ISI 304 stainless steel adjustable h 100/150 mm
redisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants

Special rack kit for drawers and shelves

Alimentazione frequenza 60Hz

Other special voltage

Half doors

Frame for fixed masonry plinth

RAL customisable colouring

Master Marine solutions

Predisposition for connection to CO2 remote

control unit

Foot pedal kit

4 Swivel and brake castors h 128 mm

Stainless steel shelf GN2/1

Plastic coated shelf GN2/1

Pair of type C slides 605 mm

Stainless steel drawer, h 150 mm 700/1400

Bottles shelf, stainless steel coating for shelf 700/1400

Serial interface, RS485 cable


Cosmo cable connection kit


Cosmo wifi connection kit


COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The cabinet, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw







A: Power supply cable outlet

D: Airflow conveyor

G: Racks pitch

P: Water drain

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.