


| Client | Quantity |
|---------|----------|
| Project | Position |

Display case for ingredients 1300 mm

Model: YP13/5NLR **Cod:** V42131100001





Technical data

| Gross capacity: | 44 lt |
|---------------------|---------------------------------|
| Temperature range: | +2°+10°C |
| Refrigerant unit: | remote |
| Cooling gas: | R452a |
| Valve: | Supplied standard with solenoid |
| Dimensions: | 1300×380×275 mm |
| Packing dimensions: | 1510×450×473 mm |
| Gross weight: | 35 Kg |
| Voltage: | 220-240 V - 50-60 Hz |
| Total rate: | 22 W |
| Absorbed Current: | 0,1 A |
| Cooling capacity: | 368 W* |
| *: | Evap10°C Cond. +55°C |

Features

| Control: | Electronic, display flush with the panel |
|------------------------------|--|
| Insulation: | 30 mm thickness - CFC/HCFC free |
| Exterior/interior finishing: | Exterior and interior AISI 304 stainless steel. |
| Inner corners: | Rounded for easy cleaning and ensuring maximum hygiene |
| Cosmo: | Predisposed for Cosmo Hub connection |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants

| Other special voltage Remote condensing unit EMT6144GK Lid for overnight storage of ingredients GN1/3 878x302x20 1300 display case pans kit, GN1/3 Wall clamps, 2 pieces Kit of 4 stainless steel feets Cosmo cable connection kit |
|--|
| Lid for overnight storage of ingredients GN1/3 878x302x20 1300 display case pans kit, GN1/3 Wall clamps, 2 pieces Kit of 4 stainless steel feets Cosmo cable connection kit |
| 878x302x20 1300 display case pans kit, GN1/3 Wall clamps, 2 pieces Kit of 4 stainless steel feets Cosmo cable connection kit |
| Wall clamps, 2 pieces Kit of 4 stainless steel feets Cosmo cable connection kit |
| Kit of 4 stainless steel feets Cosmo cable connection kit |
| Cosmo cable connection kit |
| Cosmo dable commedicini na |
| |
| Cosmo wifi connection kit |
| Pan GN1/2 325x265x150 mm |
| Lid for GN 1/2 pan |

| Pan GN1/3 325x176x150 mm | |
|-------------------------------|--|
| Lid for GN1/3 pan | |
| Pan GN1/6 176x162x150 mm | |
| Lid for GN1/6 pan | |
| Pan GN1/9 176x108x100 mm | |
| Lid for GN1/9 pan | |
| Pan GN2/8 325x132x150 mm | |
| Lid for GN2/8 pan | |
| Brackets for pans 20 mm GN1/3 | |
| Brackets for pans 25 mm GN1/3 | |
| Brackets for pans 30 mm GN1/3 | |


Remote unit technical data

| Voltage: | 220-240 V - 50 Hz |
|---------------------|----------------------|
| Cooling gas: | R404-R452 |
| Gross weight: | 17 Kg |
| Dimensions: | 450×300×270 mm |
| Packing dimensions: | 470×330×300 mm |
| Cooling capacity: | Evap10°C Cond. +55°C |


COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive wi-fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The display case for ingredients, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, Levtronic, QUBI) or with Cosmo wi-fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw







A: Power supply cable outlet

B: Condensation water drain

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.