

Client _____ Quantity _____

Project _____ Position _____

Smart Blast Chiller

Model: W10X

Cod: W11103000021



Technical data

Gross capacity:	367 lt
Temperature range:	-40°+10°C
Humidifier:	Not available
Refrigerant unit:	Plug-in
Energetic class:	/
Yield +90/+3:	45 Kg
Yield +90/-18:	30 Kg
Climate class:	5
Cooling gas:	R290 (GWP=3)
Refrigerant Charge:	150 g
Defrost:	Forced air
Valve:	Mechanical expansion
Dimensions:	780×800×1553 mm
Packing dimensions:	875×915×1826 mm
Net / gross weight:	180 Kg / 190 Kg
Net / gross volume:	/ 367 lt
Voltage:	220-240 V - 50 Hz
Total rate:	1597 W - 7,6 A
Cooling capacity:	2825 W*
*:	Evap. -10°C Cond. +40°C
Noise:	65,8 dB


Features

Functions:	Soft blast chilling, hard blast chilling, hard shock freezing, continuous cycle
Standard equipment:	10 slides GN1/1, EN60x40
Control:	Electronic, display flush with the panel
Doors:	Reversible and self-closing with anti-odour system
Door gasket:	Magnetic, triple chamber and easily replaceable
Core probe:	Needle probe with 1 reading point
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior and interior AISI 304 stainless steel.
Inner corners:	Rounded for easy cleaning, diamond-coated bottom
Handle:	In PVC
Racks and slides:	Stainless steel AISI 304, quick release
Feets:	AISI 304 stainless steel, h 18 mm

COSMO - wi-fi control

Connection to Cosmo is not available for this blast chiller model.

Technical draw



A: Power supply cable outlet

B: Condensation water drain

G: Racks pitch