

Client	Quantity
Project	Position

Clima 900 cabinet EN60×80

Model: A90/1MJ Cod: A22090200101



Clima 900 refrigerated cabinet, 1 door. Plug-in refrigeration unit, 5 heavy duty climatic class and R290 ecological refrigerant gas. Equipment: 20 pairs of slides for EN60x80 trays, lock with key, led lighting. Temperature range -2°+10°C; static-ventilated refrigeration with adjustable indirect air flow. Anti-corrosion treated evaporator, hot gas defrost. 75 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HFC free). AISI 304 stainless steel handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening with 105° stop. One-piece structure, interior/exterior AISI 304 stainless steel; outside back, external base and inside technical compartment in galvanised/colaminated steel. Rounded inner corners for easy cleaning. The reinforced modular base in colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Predisposed for connection to Cosmo remote supervision system and ModBus/RTU Rs485 connection.

Technical data

Gross capacity:	872 lt
Temperature range:	-2°+10°C
Refrigerant unit:	Plug-in
Energetic class:	В
Energy efficiency index:	32,8
Annual consumption:	537 kW/h annum
24h consumption:	1,47 kW/h/24h
Climate class:	5
Cooling gas:	R290 (GWP=3)
Refrigerant Charge:	120g
Defrost:	Hot gas
Valve:	Supplied standard with solenoid
Dimensions:	810×1015×2085 mm
Packing dimensions:	905×1130×2140 mm
Net / gross weight:	155 Kg / 165 Kg
Net / gross volume:	626 lt / 872 lt
Voltage:	220-240 V - 50 Hz
Total rate:	300W - 1,4A
Cooling capacity:	533 W*
*:	Evap10°C Cond. +55°C

Features

Standard equipment:	20 slides for EN60x80 shelves, lock with key, LED lighting
Control:	Electronic, display flush with the panel
Doors:	1 door, self-closing with a 105° stop, right hinged
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	75 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior and interior AISI 304 stainless steel. Back, base and internal technical compartment in galvanized/colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previouly or subsequently sold.



Accessories and variants

Half doors
Glass door for with led lighting
RAL customisable colouring
Plug-in water unit
Alimentazione frequenza 60Hz
Other special voltage
Foot pedal kit

4 Swivel and brake castors h 128 mm

Aluminium coated backingan EN60x40 h 20 mm

Stainless steel shelf EN60x40

Plastic coated shelf EN60x40

Pair of type L slides 755 mm EN60x80


Serial interface, RS485 cable


Cosmo cable connection kit


COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The cabinet, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw







- A: Power supply cable outlet
- D: Airflow conveyor
- G: Racks pitch

J: Automatic evaporation of condensing water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.