

| Client | Quantity |
|---------|----------|
| Project | Position |

Tavolo Master GN 1 porta BT

Model: TS09/1B-760 Cod: T10100000402



Technical data

| Тор: | Without top |
|--------------------------|---------------------------------|
| Gross capacity: | 130 lt |
| Temperature range: | -15°-22°C |
| Refrigerant unit: | Plug-in |
| Energetic class: | С |
| Energy efficiency index: | 47,2 |
| Annual consumption: | 1398 kW/h annum |
| 24h consumption: | 3,83 kW/h/24h |
| Climate class: | 5 |
| Cooling gas: | R290 (GWP=3) |
| Refrigerant Charge: | 110g |
| Defrost: | Hot gas |
| Body height: | 760 mm |
| Valve: | Supplied standard with solenoid |
| Dimensions: | 820×680×860 mm |
| Packing dimensions: | 915×800×998 mm |
| Net / gross weight: | 98 Kg / 108 Kg |
| Net / gross volume: | 100 lt / 130 lt |
| Voltage: | 220-240 V - 50 Hz |
| Total rate: | 525W - 2,4A |
| Cooling capacity: | 356 W* |
| *: | Evap30°C Cond. +55°C |

Features

| 1 slide, 1 plastic coated GN1/1 shelf |
|--|
| Electronic, display flush with the panel |
| 1 door, self-closing, reversible with 105° stop |
| Magnetic, triple chamber and easily replaceable |
| 60 mm thickness - CFC/HCFC free |
| Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. |
| Rounded for easy cleaning and ensuring maximum hygiene |
| Stainless steel AISI 304, 2 mm thick |
| Stainless steel AISI 304 |
| AISI 304 stainless steel adjustable h 100/150 mm $$ |
| Predisposed for Cosmo Hub connection |
| |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants


Drawers 1/2 Drawers 1/3 Drawers 1/3 + 2/3 Special counter body heights 650 mm Special counter body heights 700 mm Special counter body heights 750 mm Technical compartment on the left Lock with key for drawer 1/2 Lock with key for drawer 1/3 Lock with key for drawer 1/3 + 2/3 LED lighting RAL customisable colouring Plug-in water unit Alimentazione frequenza 60Hz Other special voltage Internal hygiene H3


Granite flat worktop Granite worktop with splashback Adjustable feet h 145/195 mm 4 Swivel and brake castors h 128 mm Brackets for GN pans for drawer GN1/2 container + lids kit for drawer, h 150 mm GN1/3 container + lids kit for drawer, h 150 mm Bottles shelf, stainless steel coating for shelf 350 Stainless steel shelf GN1/1 Plastic coated shelf GN1/1 Pair of type C slides 505 mm Serial interface, RS485 cable Cosmo cable connection kit Cosmo wifi connection kit IP44 schuko socket with cover Removable plinth GN 1D h 100 mm

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw







- A: Power supply cable outlet
- B: Condensation water drain
- G: Racks pitch

J: Automatic evaporation of condensing water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.