

Client	Quantity
Proiect	Position

# Master 600 counter 1 door

Model: TA09/1MQ-660 Cod: T12102000203



### **Technical data**

Тор:	With top and splashback
Gross capacity:	90 lt
Temperature range:	-2°+8°C
Refrigerant unit:	Plug-in
Energetic class:	A
Energy efficiency index:	19,7
Annual consumption:	387 kW/h annum
24h consumption:	1,06 kW/h/24h
Climate class:	5
Cooling gas:	R290 (GWP=3)
Defrost:	Hot gas
Body height:	660 mm
Valve:	Supplied standard with solenoid
Dimensions:	820×600×900 mm
Packing dimensions:	915×800×998 mm
Net / gross weight:	82 Kg / 92 Kg
Net / gross volume:	67 lt / 90 lt
Voltage:	220-240 V - 50 Hz
Total rate:	250W - 1,15A
Cooling capacity:	406 W*
*:	Evap10°C Cond. +55°C

### **Features**

Standard equipment:	1 slide, 1 plastic coated 325x430 mm shelf
Control:	Electronic, display flush with the panel
Doors:	1 door, self-closing, reversible with 105° stop
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



#### Accessories and variants


Drawers 1/2
Drawers 1/3
Drawers 1/3 + 2/3
Special counter body heights 650 mm
Special counter body heights 700 mm
Special counter body heights 750 mm
Technical compartment on the left
Lock with key for drawer 1/2
Lock with key for drawer 1/3
Lock with key for drawer 1/3 + 2/3
LED lighting
RAL customisable colouring
Plug-in water unit
Alimentazione frequenza 60Hz
Other special voltage

Internal hygiene H3	
Granite flat worktop	
Granite worktop with splashback	
Adjustable feet h 145/195 mm	
4 Swivel and brake castors h 128 mm	ı
Brackets for GN pans for drawer	
GN1/2 container + lids kit for drawer	, h 150 mm
GN1/3 container + lids kit for drawer	, h 150 mm
Plastic coated shelf 325x430	
Pair of type C slides 405 mm	
Serial interface, RS485 cable	
IP44 schuko socket with cover	
Cosmo cable connection kit	
Cosmo wifi connection kit	
Removable plinth CQ 1D h 100 mm	

### COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

## **Technical draw**



- A: Power supply cable outlet
- B: Condensation water drain
- G: Racks pitch

J: Automatic evaporation of condensing water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previouly or subsequently sold.