

Client	Quantity
Project	Position

Master 600 counter 2 doors

Model: TP13/1MQ-660 Cod: T12201000203



Technical data

Тор:	With top
Gross capacity:	210 lt
Temperature range:	-2°+8°C
Refrigerant unit:	Plug-in
Energetic class:	Α
Energy efficiency index:	20
Annual consumption:	426 kW/h annum
24h consumption:	1,167 kW/h/24h
Climate class:	5
Cooling gas:	R290 (GWP=3)
Refrigerant Charge:	110g
Defrost:	Hot gas
Body height:	660 mm
Valve:	Supplied standard with solenoid
Dimensions:	1300×600×800 mm
Packing dimensions:	1395×800×998 mm
Net / gross weight:	109 Kg / 119 Kg
Net / gross volume:	134 lt / 210 lt
Voltage:	220-240 V - 50 Hz
Total rate:	250W - 1,15A
Cooling capacity:	406 W*
*:	Evap10°C Cond. +55°C

Features

Standard equipment:	2 slides, 2 plastic coated 325x430 mm shelves
Control:	Electronic, display flush with the panel
Doors:	2 doors, self-closing, reversible with 105° stop
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants


Drawers 1/2 Drawers 1/3 Drawers 1/3 + 2/3 Special counter body heights 650 mm Special counter body heights 700 mm Special counter body heights 750 mm Technical compartment on the left Lock with key for drawer 1/2 Lock with key for drawer 1/3 Lock with key for drawer 1/3 + 2/3 LED lighting RAL customisable colouring Plug-in water unit Alimentazione frequenza 60Hz Other special voltage Internal hygiene H3


Granite flat worktop Granite worktop with splashback Service water sink Ø 300 mm Single lever mixer hole Ø 3/4 Adjustable feet h 145/195 mm 4 Swivel and brake castors h 128 mm Brackets for GN pans for drawer GN1/2 container + lids kit for drawer, h 150 mm GN1/3 container + lids kit for drawer, h 150 mm Plastic coated shelf 325x430 Pair of type C slides 405 mm Serial interface, RS485 cable IP44 schuko socket with cover Cosmo cable connection kit Cosmo wifi connection kit Removable plinth CQ 2D h 100 mm


COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw







- A: Power supply cable outlet
- B: Condensation water drain
- G: Racks pitch

J: Automatic evaporation of condensing water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.