coldline

Client	Quantity
Project	Position

Pastry EN60x40 counter 2 doors

Model: TA13/1MJR-760

Cod: T20212000202



Technical data

Тор:	With top and splashback
Gross capacity:	421 lt
Temperature range:	-2°+8°C
Refrigerant unit:	remote
Cooling gas:	R452a (GWP=2.141)
Defrost:	Electric
Body height:	760 mm
Valve:	Supplied standard with solenoid
Dimensions:	1240×800×1000 mm
Packing dimensions:	1545×900×998 mm
Net / gross weight:	116 Kg / 126 Kg
Net / gross volume:	278 lt / 421 lt
Voltage:	220-240 V - 50-60 Hz
Total rate:	810W - 3,7A
Cooling capacity:	519 W*
*:	Evap10°C Cond. +55°C

Features

Standard equipment:	8 slides EN60x40
Control:	Electronic, display flush with the panel
Doors:	2 doors, self-closing, reversible with 105° stop
Door gasket:	Magnetic, triple chamber and easily replaceable
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel.
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	Stainless steel AISI 304, 2 mm thick
Racks and slides:	Stainless steel AISI 304
Feets:	AISI 304 stainless steel adjustable h 100/150 mm
Cosmo:	Predisposed for Cosmo Hub connection

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.

coldline

Accessories and variants

Drawers 1/2	Granite flat worktop		
Drawers 1/3	Granite worktop with splashback		
Drawers 1/3 + 2/3	Remote condensing unit EMT6165GK		
Technical compartment on the left	Adjustable feet h 145/195 mm		
Common technical compartment	4 Swivel and brake castors h 128 mm		
Counters without a technical compartment	Aluminium coated backingan EN60x40 h 20 mm		
Lock with key for drawer 1/2	Stainless steel shelf EN60x40		
Lock with key for drawer 1/3	Plastic coated shelf EN60x40		
Lock with key for drawer $1/3 + 2/3$	Pair of type L slides 605 mm		
RAL customisable colouring	R134a valve		
Stainless steel evaporator	Serial interface, RS485 cable		
Predisposition for connection to CO2 remote control unit	Cosmo cable connection kit		
	Cosmo wifi connection kit		
Alimentazione frequenza 60Hz	Removable plinth EN 2DR h 100 mm		
Other special voltage	Removable plinth EN 2DR h 150 mm		
Internal hygiene H3	·		


Remote unit technical data

Voltage:	220-240 V - 50 Hz
Assorbimento Unità Remota:	330W - 1,5A
Cooling gas:	R452A
Gross weight:	17 Kg
Dimensions:	450×300×270 mm
Pipe delivery:	Ø 1/4"
Pipe suction:	Ø 3/8"
Packing dimensions:	470×330×300 mm
Cooling capacity:	Evap10°C Cond. +55°C

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw



A:	Power supply cable outlet	В:	Condensation water drain	G:	Racks pitch

J: Automatic evaporation of R: Gas output pipes condensing water

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previosly or subsequently sold.