

| Client | Quantity |
|---------|----------|
| Project | Position |

Prep-station EN60x40 counter 2 doors

Model: TVG13/1MZR-1/6-710 Cod: T20213000231



Technical data

| With top |
|---------------------------------|
| 389 lt |
| -2°+8°C |
| remote |
| R452a (GWP=2.141) |
| Electric |
| 710 mm |
| Supplied standard with solenoid |
| 1240×800×1005 mm |
| 1545×900×998 mm |
| 130 Kg / 140 Kg |
| / 389 lt |
| 220-240 V - 50-60 Hz |
| 810W - 3,7A |
| 519 W* |
| Evap10°C Cond. +55°C |
| |

Rosa Beta granite top. Remote refrigeration unit, 5 heavy duty climatic class and R452a refrigerant gas. Temperature range -2°+8°C with ventilated refrigeration. Refrigerated container for GN1/6 bowls with opening lid. Equipment: 2 EN60x40 plastic coated shelves. Each compartment can be configured with 1/2+1/2, 1/3+2/3, 1/3+1/3+1/3 drawers. Anti-corrosion treated evaporator and electric defrosting. 60 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). AISI 304 stainless steel handle and magnetic triple chamber door gasket, easily replaceable. Reversible, self-closing door opening with 105° stop. AISI 304 stainless steel interior/exterior including external back. Rounded inner corners for easy cleaning. The reinforced modular base in colaminated steel allows installation on wheels, feet, mobile or masonry plinths. Replaceable refrigerant system FSS - Fast Service System - for quick and easy service. Prepared for connection to Cosmo - wi-fi remote supervision system - and ModBus/RTU Rs485 connection.

Prep-Station 800 refrigerated counter 2 doors, counter body height 710 mm, with

Features

| Standard equipment: | 2 slides, 2 plastic coated EN60x40 shelves |
|------------------------------|--|
| Control: | Electronic, display flush with the panel |
| Doors: | 2 doors, self-closing, reversible with 105° stop |
| Door gasket: | Magnetic, triple chamber and easily replaceable |
| Insulation: | 60 mm thickness - CFC/HCFC free |
| Exterior/interior finishing: | Exterior interior and back in AISI 304 stainless steel. Base in colaminated steel. |
| Inner corners: | Rounded for easy cleaning and ensuring maximum hygiene |
| Lid hinges: | Made of black plastic |
| Handle: | Stainless steel AISI 304, 2 mm thick |
| Racks and slides: | Stainless steel AISI 304 |
| Feets: | AISI 304 stainless steel adjustable h 100/150 mm |
| Cosmo: | Predisposed for Cosmo Hub connection |
| | |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previouly or subsequently sold.



Accessories and variants

| Drawers 1/2 |
|--|
| Drawers 1/3 |
| Drawers 1/3 + 2/3 |
| Special counter body heights 700 mm |
| Special counter body heights 750 mm |
| Technical compartment on the left |
| Common technical compartment |
| Special size of technical compartment |
| Lock with key for drawer 1/2 |
| Lock with key for drawer 1/3 |
| Lock with key for drawer 1/3 + 2/3 |
| LED lighting |
| RAL customisable colouring |
| Predisposition for connection to CO2 remote control unit |
| Alimentazione frequenza 60Hz |
| Other special voltage |
| Remote condensing unit EMT6165GK |

| Adjustable feet h 145/195 mm | |
|--|----|
| 4 Swivel and brake castors h 128 mm | |
| EN drawer reduction kit for GN containers | |
| Brackets for GN pans for drawer | |
| GN1/2 container + lids kit for drawer, h 150 | mm |
| GN1/3 container + lids kit for drawer, h 150 | mm |
| Stainless steel shelf EN60x40 | |
| Plastic coated shelf EN60x40 | |
| Pair of type L slides 605 mm | |
| Serial interface, RS485 cable | |
| Cosmo cable connection kit | |
| Cosmo wifi connection kit | |
| Prep-Station pans kit GN1/6 remote, 2D | |
| Prep-Station pans kit GN1/6 remote, 2D EN | |
| Removable plinth EN 2DR h 100 mm | |
| Removable plinth EN 2DR h 150 mm | |
| R134a valve | |


Remote unit technical data

| Voltage: | 220-240 V - 50 Hz |
|----------------------------|----------------------|
| Assorbimento Unità Remota: | 330W - 1,5A |
| Cooling gas: | R452A |
| Gross weight: | 17 Kg |
| Dimensions: | 450×300×270 mm |
| Pipe delivery: | Ø 1/4" |
| Pipe suction: | Ø 3/8" |
| Packing dimensions: | 470×330×300 mm |
| Cooling capacity: | Evap10°C Cond. +55°C |

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The counter, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw



- A: Power supply cable outlet
- B: Condensation water drain
- D: Airflow conveyor

G: Racks pitch

- J: Automatic evaporation of condensing water
- R: Gas output pipes

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.