

Client	Quantity
Project	Position

Modi Up Blast Chiller

Model: W6ULR Cod: W51065000001



Technical data

Тор:	Thickness 4 cm. Reinforced in order to place an oven
Max capacity:	6 basins 360x165x150 mm or 6 ice cream containers Ø 200x200x125 mm
Gross capacity:	160 lt
Temperature range:	-40°+10°C
Ventilation range:	25% - 100%
Humidifier:	Not available
Refrigerant unit:	remote
Yield +90/+3:	28 Kg
Yield +90/-18:	23 Kg
Cooling gas:	R452a (GWP=2.141)
Defrost:	Forced air
Valve:	Electronic expansion valve
Dimensions:	780×800×913 mm
Packing dimensions:	875×915×1141 mm
Net / gross weight:	95 Kg / 105 Kg
Net / gross volume:	/ 160 lt
Voltage:	220-240 V - 50-60 Hz
Total rate:	100 W - 0,48 A
Cooling capacity:	2084 W*
*.	Evap10°C Cond. +45°C

Modi multifunction blast chiller 6 trays Up version (6 basins 360x165x150 mm), depth 800 mm, temperature range -40°+10°C. It is equipped with the functions: blast chilling, blast freezing, manual cycle. Remote cooling system with R452a $\,$ refrigerant gas. 4,3" touch screen on the door and operating mode with customisable recipes, by time or with core probe. Adjustable ventilation 25-100%. Blast chilling yield +90/+3°C - 28 Kg; blast freezing yield +90/-18°C - 23 Kg. 5 heavy duty climatic class, forced air defrost. 60 mm insulation thickness - HFO with high insulation performance and low environmental impact (CFC, HCFC, HFC free). Electronic expansion valve and anti-corrosion painted evaporator. Cushioned door with anti-odour system with Easily replaceable triple chamber magnetic gasket, core probe with screw connector and housing on the port. Exterior and interior AISI 304 stainless steel, fan unit and condenser cover removable without tools. Equipment: 1 pair of slides and 1 EN60x40 plastic coated shelf. ModBus/RTU Rs485 connection as standard. Cosmo: wi-fi connection for remote monitoring via Cosmo App. When wired to Coldline counters and cabinets acts as a hub for remote monitoring of connected equipment.

Features

Blast chilling, shock freezing, continuous cycle
1 slide EN60x40, 1 plastic coated EN60x40 shelf
4,3" touch screen display with USB port
Cushioned, with anti-odor system
Magnetic, triple chamber and easily replaceable
Needle probe with 1 reading point, quick-release and easily replaceable
60 mm thickness - CFC/HCFC free
Exterior and interior AISI 304 stainless steel.
Rounded for easy cleaning and ensuring maximum hygiene
Stainless steel AISI 304, 2 mm thick
Stainless steel AISI 304, quick release
AISI 304 stainless steel adjustable h 100/150 mm
Wi-Fi remote control system

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previouly or subsequently sold.



Accessories and variants

RAL customisable colouring

Sonda al cuore a 3 punti di lettura

Sonda al cuore riscaldata a 1 punto di lettura

Reverse door opening from standard

Predisposition for connection to CO2 remote control unit

Other special voltage

Remote condensing unit W6-W7T

Lowered foot h 55/70 mm
4 Swivel and brake castors h 128 mm
Aluminium coated backingan EN60x40 h 20 mm
Stainless steel shelf EN60x40
Plastic coated shelf EN60x40
Pair of type L slides 398 mm EN
Sterilizing UV lamp


Remote unit technical data

Voltage:	220-240 V - 50 Hz
Cooling gas:	R404-R452a
Gross weight:	31 Kg
Dimensions:	780×752×280 mm
Pipe delivery:	10 mm
Pipe suction:	10 mm
Cooling capacity:	Evap10°C Cond. +45°C

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows MODI blast chillers to be connected, updated and monitored from smartphones. MODI is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

Technical draw



In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.