

Client _____ Quantity _____

Project _____ Position _____

Vision Industry W102K U

Model: W102KUR-2D

Cod: W80220216001



Technical data

| | |
|---------------------|----------------------------|
| Max capacity: | 2 trolleys |
| Temperature range: | -40°+10°C |
| Ventilation range: | 25% - 100% |
| Humidifier: | Not available |
| Refrigerant unit: | remote |
| Yield +90/+3: | 520 Kg |
| Yield +90/-18: | 400 Kg |
| Cooling gas: | R404/R452 |
| Defrost: | Forced air |
| Valve: | Electronic expansion valve |
| Dimensions: | 1600×2600×2510 mm |
| Packing dimensions: | 2735×1735×2550 mm |
| Net / gross weight: | 776 Kg / 856 Kg |
| Net / gross volume: | / |
| Voltage: | 400-415 V - 50-60 Hz |
| Total rate: | 4270 W - 8,64 A |
| Cooling capacity: | 45960 W* |
| *: | Evap. -10°C Cond. +45°C |

Features

| | |
|------------------------------|--|
| Functions: | Blast chilling, shock freezing, continuous cycle |
| Control: | 7" touch screen display with USB port |
| Doors: | Dictator closure to absorb sudden changes in pressure when opening and closing doors |
| Door gasket: | Magnetic, triple chamber and easily replaceable |
| Core probe: | Needle probe with 1 reading point, quick-release and easily replaceable |
| Insulation: | 100 mm thickness - CFC/HCFC free |
| Exterior/interior finishing: | Internal and external in "linen canvas" steel |
| Inner corners: | Rounded base 20 mm |
| Handle: | In AISI 304 stainless steel |
| Cosmo: | Wi-Fi remote control system |

Accessories and variants

| | |
|--|--|
| Abbattitore fornito smontato | Silenced faired remote condensing unit 4FE-28Y |
| Floor 20 mm high, ramp included | Faired unit with remote condenser 4FE-28Y |
| Reverse door opening from standard | PVC ventilation profiles W100K |
| Door opening turning and control panel inversion | Ramp 100 mm high. Length 913 mm W40 |
| Door stop 100° | Ramp 140 mm high. Length 1390 mm W40 |
| Sonda al cuore 3 punti di lettura | Trolley GN1/1 20 trays 598x530x1630 mm |
| Sonda al cuore riscaldata 1 punto di lettura | Trolley EN60x40 20 trays 460x620x1750 mm |
| Winter kit -20°C | Trolley GN2/1 20 trays 660x720x1750 mm |
| Winter kit -40°C | Trolley EN60x80 20 trays 660x820x1750 mm |
| Predisposition for connection to CO2 remote control unit | Purity C Quell ST 50 filter cartridge |
| Other special voltage | Sanitizing detergent |


Remote unit technical data

| | |
|----------------------------|-------------------------|
| Voltage: | 400-415 V 3N - 50 Hz |
| Assorbimento Unità Remota: | 20,8kW - 37,2A |
| Cooling gas: | R404-R452a |
| HP unit: | 28 |
| Gross weight: | 950 Kg |
| Dimensions: | 2200×1300×1800 mm |
| Pipe delivery: | 12 mm |
| Pipe suction: | 42 mm |
| Cooling capacity: | Evap. -10°C Cond. +45°C |

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows VISION blast chillers to be connected, updated and monitored from smartphones. VISION is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

Technical draw



| | | | | | |
|----|---------------------------|----|---|----|--|
| A: | Power supply cable outlet | B: | Condensation water drain | C: | Floor grid for condensate drainage (recommended) |
| I: | Internal led lighting | L: | Door clear opening dimension | N: | PVC ventilation profiles |
| R: | Gas output pipes | W: | Water mains connection for humidifier - 3/4" female. Unloading not required | | |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.