

| Client | Quantity |
|---------|----------|
| Project | Position |

Armadio Master 700 BT

Model: A70/1BS Cod: A14076600101



Technical data

| | (04 l) |
|--------------------------|---------------------------------|
| Gross capacity: | 601 lt |
| Temperature range: | -18°-22°C |
| Refrigerant unit: | Plug-in |
| Energetic class: | D |
| Energy efficiency index: | 49,5 |
| Annual consumption: | 2919 kW/h annum |
| 24h consumption: | 7,997 kW/h/24h |
| Climate class: | 5 |
| Cooling gas: | R290 (GWP=3) |
| Refrigerant Charge: | 150g |
| Defrost: | Hot gas |
| Valve: | Supplied standard with solenoid |
| Dimensions: | 740×815×2085 mm |
| Packing dimensions: | 835×930×2138 mm |
| Net / gross weight: | 140 Kg / 160 Kg |
| Net / gross volume: | 450 lt / 601 lt |
| Voltage: | 220-240 V - 50 Hz |
| Total rate: | 1000W - 4,6A |
| Cooling capacity: | 692 W* |
| *: | Evap30°C Cond. +55°C |
| | |

Features

| 3 slides for GN2/1 shelves, 3 plastic coated GN2/1 shelves, lock with key, LED lighting |
|--|
| Electronic, display flush with the panel |
| 1 door, self-closing with a 105° stop, right hinged |
| Magnetic, triple chamber and easily replaceable |
| 75 mm thickness - CFC/HCFC free |
| Exterior and interior AISI 304 stainless steel. Back, base and internal technical compartment in galvanized/colaminated steel. |
| Rounded for easy cleaning and ensuring maximum hygiene |
| Stainless steel AISI 304, 2 mm thick |
| Stainless steel AISI 304 |
| AISI 304 stainless steel adjustable h 100/150 mm |
| Predisposed for Cosmo Hub connection |
| |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.



Accessories and variants

Special rack kit for drawers and shelves

Alimentazione frequenza 60Hz

Other special voltage

Half doors

Frame for fixed masonry plinth

RAL customisable colouring

Master Marine solutions

Predisposition for connection to CO2 remote

control unit

Plug-in water unit

Foot pedal kit

4 Swivel and brake castors h 128 mm

Stainless steel shelf GN2/1

Plastic coated shelf GN2/1

Pair of type C slides 605 mm

Stainless steel drawer, h 150 mm 700/1400

Bottles shelf, stainless steel coating for shelf

700/1400


Serial interface, RS485 cable


Cosmo cable connection kit


COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows Coldline, Modular and Nevo appliances to be connected and monitored from a smartphone. The cabinet, connected with Cosmo kit via cable to a Cosmo hub (MODI, VISION, THAW.PRO, LEVTRONIC, QUBI) or with Cosmo Wi-Fi kit, can be monitored by the CosmoApp and receive alerts in case of abnormal operation.

Technical draw









A: Power supply cable outlet

D: Airflow conveyor

G: Racks pitch

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.