

Client _____ Quantity _____

Project _____ Position _____

Vision Industry W30K U

Model: W30KU

Cod: W83111112001



Technical data

Max capacity:	1 trolley
Temperature range:	-40°+10°C
Ventilation range:	25% - 100%
Humidifier:	Not available
Refrigerant unit:	Plug-in
Yield +90/+3:	90 Kg
Yield +90/-18:	66 Kg
Climate class:	5
Cooling gas:	R404/R452
Refrigerant Charge:	5000g
Defrost:	Forced air
Valve:	Electronic expansion valve
Dimensions:	960×1276×2595 mm
Packing dimensions:	1050×1300×2745 mm
Net / gross weight:	290 Kg / 300 Kg
Net / gross volume:	/
Voltage:	400-415 V - 50 Hz
Total rate:	6150 W - 10,9 A
Cooling capacity:	7751 W*
*:	Evap. -10°C Cond. +45°C

Features

Functions:	Blast chilling, shock freezing, continuous cycle
Control:	7" touch screen display with USB port
Doors:	Cushioned, with anti-odor system
Door gasket:	Magnetic, triple chamber and easily replaceable
Core probe:	Needle probe with 1 reading point, quick-release and easily replaceable
Insulation:	60 mm thickness - CFC/HCFC free
Exterior/interior finishing:	AISI 304 stainless steel exterior and interior
Inner corners:	Rounded for easy cleaning and ensuring maximum hygiene
Handle:	In AISI 304 stainless steel
Racks and slides:	Stainless steel AISI 304, quick release
Cosmo:	Wi-Fi remote control system

Accessories and variants

Reverse door opening from standard

Door stop 100°

Sonda al cuore 3 punti di lettura

Sonda al cuore riscaldata 1 punto di lettura

Winter kit -20°C

Winter kit -40°C

Other special voltage

Trolley GN1/1 20 trays 598x530x1630 mm


Trolley EN60x40 20 trays 460x620x1750 mm

Purity C Quell ST 50 filter cartridge

COSMO - wi-fi control

Cosmo is The Nice Kitchen's exclusive Wi-Fi technology that allows VISION blast chillers to be connected, updated and monitored from smartphones. VISION is also a Cosmo hub and allows remote supervision of the Coldline appliances connected to it. From the CosmoApp you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

Technical draw



A: Power supply cable outlet

B: Condensation water drain

I: Internal led lighting

R: Gas output pipes